Doctrine 1.0

License: Creative Commons Attribution-Share Alike 3.0 Unported License

Version: cookbook-1.0-de-2010-05-12

SENSIOLABS

Table of Contents

My First Project ... 3
Introduction ... 3
Download ... 3
Package Contents ... 3
Running the CLI ... 4
Defining Schema ... 4
Test Data Fixtures ... 5
Building Everything ... 5
Running Tests ... 6
User CRUD ... 8

symfony and Doctrine ... 10
Setup ... 10
Setup Database ... 11
Setup Schema ... 11
Build Database ... 12
Admin Generators ... 13
Helpful Links ... 14

symfony Doctrine Migrations ... 16

Code Igniter and Doctrine ... 17
Download Doctrine ... 17
Setup Doctrine ... 17
Setup Command Line Interface ... 18
Start Using Doctrine ... 20

Chapter 1

My First Project

Introduction

This is a tutorial & how-to on creating your first project using the fully featured PHP Doctrine ORM. This tutorial
uses the the ready to go Doctrine sandbox package. It requires a web server, PHP and PDO + Sqlite.

Download

To get started, first download the latest Doctrine sandbox package: http://www.phpdoctrine.org/download[1]. Second, extract
the downloaded file and you should have a directory named Doctrine-x.x.x-Sandbox. Inside of that directory is a simple
example implementation of a Doctrine based web application.

Package Contents

The files/directory structure should look like the following

Listing 1-1

```
$ cd Doctrine-0.10.1-Sandbox
$ ls
config.php    doctrine    index.php    migrations    schema
data        doctrine.php    lib        models
```

The sandbox does not require any configuration, it comes ready to use with a sqlite database. Below is a description of
each of the files/directories and what its purpose is.

- doctrine - Shell script for executing the command line interface. Run with ./doctrine to see a list of command or

./doctrine help to see a detailed list of the commands

- doctrine.php - Php script which implements the Doctrine command line interface which is included in the above doctrine

1. http://www.phpdoctrine.org/download

shell script

- index.php - Front web controller for your web application
- migrations - Folder for your migration classes
- schema - Folder for your schema files
- models - Folder for your model files
- lib - Folder for the Doctrine core library files

Running the CLI

If you execute the doctrine shell script from the command line it will output the following:

Listing 1-2

```
$ ./doctrine
Doctrine Command Line Interface

./doctrine build-all
./doctrine build-all-load
./doctrine build-all-reload
./doctrine compile
./doctrine create-db
./doctrine create-tables
./doctrine dql
./doctrine drop-db
./doctrine dump-data
./doctrine generate-migration
./doctrine generate-migrations-db
./doctrine generate-migrations-models
./doctrine generate-models-db
./doctrine generate-models-yaml
./doctrine generate-sql
./doctrine generate-yaml-db
./doctrine generate-yaml-models
./doctrine load-data
./doctrine migrate
./doctrine rebuild-db
```

Defining Schema

Below is a sample yaml schema file to get started. You can place the yaml file in schemas/schema.yml. The command
line interface looks for all *.yml files in the schemas folder.

Listing 1-3

```
---
User:
  columns:
    id:
      primary: true
      autoincrement: true
      type: integer(4)
    username: string(255)
    password: string(255)
  relations:
    Groups:
      class: Group
      refClass: UserGroup
```

```
      foreignAlias: Users

Group:
  tableName: groups
  columns:
    id:
      primary: true
      autoincrement: true
      type: integer(4)
    name: string(255)

UserGroup:
  columns:
    user_id: integer(4)
    group_id: integer(4)
  relations:
    User:
      onDelete: CASCADE
    Group:
      onDelete: CASCADE
```

Test Data Fixtures

Below is a sample yaml data fixtures file. You can place this file in data/fixtures/data.yml. The command line
interface looks for all *.yml files in the data/fixtures folder.

Listing 1-4

```
---
User:
  zyne:
    username: zYne-
    password: changeme
    Groups: [founder, lead, documentation]
  jwage:
    username: jwage
    password: changeme
    Groups: [lead, documentation]

Group:
  founder:
    name: Founder
  lead:
    name: Lead
  documentation:
    name: Documentation
```

Building Everything

Now that you have written your schema files and data fixtures, you can now build everything and begin working with your
models . Run the command below and your models will be generated in the models folder.

Listing 1-5

```
$ ./doctrine build-all-reload
build-all-reload - Are you sure you wish to drop your databases? (y/n)
y
```

```
build-all-reload - Successfully dropped database for connection "sandbox"
at path "/Users/jwage/Sites/doctrine/branches/0.10/tools/sandbox/
sandbox.db"
build-all-reload - Generated models successfully from YAML schema
build-all-reload - Successfully created database for connection "sandbox"
at path "/Users/jwage/Sites/doctrine/branches/0.10/tools/sandbox/
sandbox.db"
build-all-reload - Created tables successfully
build-all-reload - Data was successfully loaded
```

Take a peak in the models folder and you will see that the model classes were generated for you. Now you can begin coding
in your index.php to play with Doctrine itself. Inside index.php place some code like the following for a simple test.

Running Tests

Listing 1-6

```
$query = new Doctrine_Query();
$query->from('User u, u.Groups g');

$users = $query->execute();

echo '<pre>';
print_r($users->toArray(true));
```

The print_r() should output the following data. You will notice that this is the data that we populated by placing
the yaml file in the data/fixtures files. You can add more data to the fixtures and rerun the build-all-reload
command to reinitialize the database.

Listing 1-7

```
Array
(
    [0] => Array
        (
            [id] => 1
            [username] => zYne-
            [password] => changeme
            [Groups] => Array
                (
                    [0] => Array
                        (
                            [id] => 1
                            [name] => Founder
                        )

                    [1] => Array
                        (
                            [id] => 2
                            [name] => Lead
                        )

                    [2] => Array
                        (
                            [id] => 3
                            [name] => Documentation
```

```
                        )

                )

        )

    [1] => Array
        (
            [id] => 2
            [username] => jwage
            [password] => changeme
            [Groups] => Array
                (
                    [0] => Array
                        (
                            [id] => 2
                            [name] => Lead
                        )

                    [1] => Array
                        (
                            [id] => 3
                            [name] => Documentation
                        )

                )

        )

)
```

You can also issue DQL queries directly to your database by using the dql command line function. It is used like the
following.

Listing 1-8

```
jwage:sandbox jwage$ ./doctrine dql "FROM User u, u.Groups g"
dql - executing: "FROM User u, u.Groups g" ()
dql - -
dql -   id: 1
dql -   username: zYne-
dql -   password: changeme
dql -   Groups:
dql -     -
dql -       id: 1
dql -       name: Founder
dql -     -
dql -       id: 2
dql -       name: Lead
dql -     -
dql -       id: 3
dql -       name: Documentation
dql - -
dql -   id: 2
dql -   username: jwage
dql -   password: changeme
dql -   Groups:
dql -     -
dql -       id: 2
```

```
dql -       name: Lead
dql -     -
dql -       id: 3
dql -       name: Documentation
```

User CRUD

Now we can demonstrate how to implement Doctrine in to a super simple module for managing users and passwords. Place
the following code in your index.php and pull it up in your browser. You will see the simple application.

Listing 1-9

```
require_once('config.php');

Doctrine::loadModels('models');

$module = isset($_REQUEST['module']) ? $_REQUEST['module']:'users';
$action = isset($_REQUEST['action']) ? $_REQUEST['action']:'list';

if ($module == 'users') {
    $userId = isset($_REQUEST['id']) && $_REQUEST['id'] > 0 ?
$_REQUEST['id']:null;
    $userTable = Doctrine::getTable('User');

    if ($userId === null) {
        $user = new User();
    } else {
        $user = $userTable->find($userId);
    }

    switch ($action) {
        case 'edit':
        case 'add':
            echo '<form action="index.php?module=users&action=save"
method="POST">
                  <fieldset>
                    <legend>User</legend>
                    <input type="hidden" name="id" value="' . $user->id .
'" />
                    <label for="username">Username</label> <input
type="text" name="user[username]" value="' . $user->username . '" />
                    <label for="password">Password</label> <input
type="text" name="user[password]" value="' . $user->password . '" />
                    <input type="submit" name="save" value="Save" />
                  </fieldset
                  </form>';
            break;
        case 'save':
            $user->merge($_REQUEST['user']);
            $user->save();

            header('location: index.php?module=users&action=edit&id=' .
$user->id);
            break;
        case 'delete':
            $user->delete();
```

```
            header('location: index.php?module=users&action=list');
            break;
        default:
            $query = new Doctrine_Query();
            $query->from('User u')
                  ->orderby('u.username');

            $users = $query->execute();

            echo '<ul>';
            foreach ($users as $user) {
                echo '<li><a href="index.php?module=users&action=edit&id='
. $user->id . '">' . $user->username . '</a>   <a
href="index.php?module=users&action=delete&id=' . $user->id .
'">[X]</a></li>';
            }
            echo '</ul>';
    }

    echo '<ul>
            <li><a href="index.php?module=users&action=add">Add</a></li>
            <li><a href="index.php?module=users&action=list">List</a></li>
          </ul>';
} else {
    throw new Exception('Invalid module');
}
```

Chapter 2

symfony and Doctrine

So, you want to give Doctrine a try with symfony 1.1 eh? First we will need to setup a new symfony 1.1 project and install the sfDoctrinePlugin for 1.1. Execute the following commands below and continue reading:

Setup

Listing 2-1

```
$ mkdir symfony1.1Doctrine
$ cd symfony1.1Doctrine
$ /path/to/symfony generate:project symfony1.1Doctrine
$ svn co http://svn.symfony-project.com/plugins/sfDoctrinePlugin/trunk
plugins/sfDoctrinePlugin
$ php symfony cc
```

Now, type the following command to list all the new commands that `sfDoctrinePlugin` provides. You will notice that it gives you all the same commands as `sfPropelPlugin` and lots more!

Listing 2-2

```
$ php symfony list doctrine
Available tasks for the "doctrine" namespace:
  :build-all                    Generates Doctrine model, SQL and
initializes the database (doctrine-build-all)
  :build-all-load               Generates Doctrine model, SQL, initializes
database, and load data (doctrine-build-all-load)
  :build-all-reload             Generates Doctrine model, SQL, initializes
database, and load data (doctrine-build-all-reload)
  :build-all-reload-test-all    Generates Doctrine model, SQL, initializes
database, load data and run all test suites
(doctrine-build-all-reload-test-all)
  :build-db                     Creates database for current model
(doctrine-build-db)
  :build-forms                  Creates form classes for the current model
(doctrine-build-forms)
  :build-model                  Creates classes for the current model
(doctrine-build-model)
  :build-schema                 Creates a schema.xml from an existing
database (doctrine-build-schema)
  :build-sql                    Creates SQL for the current model
(doctrine-build-sql)
  :data-dump                    Dumps data to the fixtures directory
(doctrine-dump-data)
  :data-load                    Loads data from fixtures directory
```

```
(doctrine-load-data)
  :dql                          Execute a DQL query and view the results
(doctrine-dql)
  :drop-db                      Drops database for current model
(doctrine-drop-db)
  :generate-crud                Generates a Doctrine CRUD module
(doctrine-generate-crud)
  :generate-migration           Generate migration class
(doctrine-generate-migration)
  :generate-migrations-db       Generate migration classes from existing
database connections (doctrine-generate-migrations-db,
doctrine-gen-migrations-from-db)
  :generate-migrations-models   Generate migration classes from an existing
set of models (doctrine-generate-migrations-models,
doctrine-gen-migrations-from-models)
  :init-admin                   Initializes a Doctrine admin module
(doctrine-init-admin)
  :insert-sql                   Inserts SQL for current model
(doctrine-insert-sql)
  :migrate                      Migrates database to current/specified
version (doctrine-migrate)
  :rebuild-db                   Creates database for current model
(doctrine-rebuild-db)
```

First, `sfDoctrinePlugin` currently requires that at least one application be setup, so lets just instantiate a `frontend` application now.

```
$ php symfony generate:app frontend
```

Listing 2-3

Setup Database

Now lets setup our database configuration in `config/databases.yml`. Open the file in your favorite editor and place the YAML below inside. For this test we are simply using a SQLite database. Doctrine is able to create the SQLite database at the `config/doctrine.db` path for you which we will do once we setup our schema and some data fixtures.

```
---
all:
  doctrine:
    class:    sfDoctrineDatabase
    param:
      dsn:    sqlite
```

Listing 2-4

Setup Schema

Now that we have our database configured, lets define our YAML schema files in `config/doctrine/schema.yml`. In this example we are setting up a simple `BlogPost` model which `hasMany` `Tags`.

```
---
BlogPost:
  actAs:
    Sluggable:
      fields: [title]
```

Listing 2-5

```
    Timestampable:
  columns:
    title: string(255)
    body: clob
    author: string(255)
  relations:
    Tags:
      class: Tag
      refClass: BlogPostTag
      foreignAlias: BlogPosts

BlogPostTag:
  columns:
    blog_post_id:
      type: integer
      primary: true
    tag_id:
      type: integer
      primary: true

Tag:
  actAs: [Timestampable]
  columns:
    name: string(255)
```

Now that we have our Doctrine schema defined, lets create some test data fixtures in `data/fixtures/data.yml`. Open the file in your favorite editor and paste the below YAML in to the file.

Listing 2-6

```
---
BlogPost:
  BlogPost_1:
    title:  symfony + Doctrine
    body:   symfony and Doctrine are great!
    author: Jonathan H. Wage
    Tags:   [symfony, doctrine, php]

Tag:
  symfony:
    name: symfony
  doctrine:
    name: doctrine
  php:
    name: php
```

Build Database

Ok, now for the fun stuff. We have our schema, and we have some data fixtures, so lets run one single Doctrine command and create your database, generate your models, create tables and load the data fixtures.

Listing 2-7

```
$ php symfony doctrine-build-all-reload frontend
>> doctrine  Are you sure you wish to drop your databases? (y/n)
y
>> doctrine  Successfully dropped database f...1.1Doctrine/config/
doctrine.db"
```

```
>> doctrine  Successfully created database f...1.1Doctrine/config/
doctrine.db"
>> doctrine  Generated models successfully
>> doctrine  Created tables successfully
>> doctrine  Data was successfully loaded
```

Now your `doctrine.db` SQLite database is created, all the tables for your schema were created, and the data fixtures were populated in to the tables. Now lets do a little playing around with the data to see how we can use the Doctrine Query Language to retrieve data.

Listing 2-8

```
$ php symfony doctrine:dql frontend "FROM BlogPost p, p.Tags t"
>> doctrine  executing: "FROM BlogPost p, p.Tags t" ()
>> doctrine  -
>> doctrine    id: 1
>> doctrine    title: symfony + Doctrine
>> doctrine    body: symfony and Doctrine are great!
>> doctrine    author: Jonathan H. Wage
>> doctrine    slug: symfony-doctrine
>> doctrine    created_at: 2008-06-16 12:28:57
>> doctrine    updated_at: 2008-06-16 12:28:57
>> doctrine    Tags:
>> doctrine      -
>> doctrine        id: 1
>> doctrine        name: symfony
>> doctrine        created_at: 2008-06-16 12:28:57
>> doctrine        updated_at: 2008-06-16 12:28:57
>> doctrine      -
>> doctrine        id: 2
>> doctrine        name: doctrine
>> doctrine        created_at: 2008-06-16 12:28:57
>> doctrine        updated_at: 2008-06-16 12:28:57
>> doctrine      -
>> doctrine        id: 3
>> doctrine        name: php
>> doctrine        created_at: 2008-06-16 12:28:57
>> doctrine        updated_at: 2008-06-16 12:28:57
```

Now, lets do a little explaining of the data that was returned. As you can see the models have a created_at, updated_at and slug column which were not defined in the schema files. These columns are added by the behaviors attached to the schema information under the actAs setting. The `created_at` and `updated_at` column are automatically set `onInsert` and `onUpdate`, and the slug column is a url friendly string that is created from the value of the name column. Doctrine has a few behaviors that are included in core such as `Sluggable` and `Timestampable`, but the behavior system is built to allow anyone to easily write behaviors for their models to re-use over and over.

Admin Generators

Now we have our data model all setup and populated with some test fixtures so lets generate an admin generator to manage the blog posts and tags.

Listing 2-9

```
$ php symfony doctrine:init-admin frontend blog_posts BlogPost
$ php symfony doctrine:init-admin frontend tags Tag
```

Now go open up your web browser and check out the `frontend` application and the `blog_posts` and `tags` modules. It should be located at a url like the following:

Listing 2-10
```
http://localhost/symfony1.1Doctrine/web/frontend_dev.php/blog_posts
http://localhost/symfony1.1Doctrine/web/frontend_dev.php/tags
```

Now, with a little configuration of the blog post admin generator, we can control the associated blog post tags by checking checkboxes when editing a blog post. Open `apps/frontend/modules/blog_posts/config/generator.yml` and replace the contents with the YAML from below.

Listing 2-11
```
---
generator:
  class:              sfDoctrineAdminGenerator
  param:
    model_class:      BlogPost
    theme:            default
    list:
      display:        [=title, author]
      object_actions:
        _edit:        -
        _delete:      -
    edit:
      display:        [author, title, body, Tags]
      fields:
        author:
          type:       input_tag
        title:
          type:       input_tag
        body:
          type:       textarea_tag
          params:     size=50x10
        Tags:
          type:       doctrine_admin_check_list
          params:     through_class=BlogPostTag
```

Now refresh the blog post list and you will see it is cleaned up a little bit. Edit a blog post by clicking the edit icon or the title and you can see below you can check the tags associated to the blog post.

All of the features you get in Propel work 99% the same way with Doctrine, so it should be fairly easy to get the hang of if you are coming from propel. sfDoctrinePlugin implements all the same functionality as sfPropelPlugin as well as several additional features which sfPropelPlugin is not capable of. Below you can find some more information on the major features that Doctrine supports:

Helpful Links

- Behaviors - http://www.phpdoctrine.org/documentation/manual/0_11?chapter=plugins[2] - Easily create reusable behaviors for your Doctrine models.
- Migrations - http://www.phpdoctrine.org/documentation/manual/0_11?chapter=migration[3] - Deploy database schema changes to your production environment through a programmatic interface.

2. http://www.phpdoctrine.org/documentation/manual/0_11?chapter=plugins
3. http://www.phpdoctrine.org/documentation/manual/0_11?chapter=migration

- Doctrine Query Language - http://www.phpdoctrine.org/documentation/manual/0_11?chapter=dql-doctrine-query-language[4] - Build your database queries through a fluent OO interface
- Validators - http://www.phpdoctrine.org/documentation/manual/0_11?chapter=basic-schema-mapping#constraints-and-validators[5] - Turn on column validators for both database and code level validation.
- Hierarchical Data http://www.phpdoctrine.org/documentation/manual/0_11?chapter=hierarchical-data[6] - Turn your models in to nested sets easily with the flip of a switch.
- Caching http://www.phpdoctrine.org/documentation/manual/0_11?chapter=caching[7] - Tune performance by caching your DQL query parsing and the result sets of queries.

If this short tutorial sparked your interest in Doctrine you can check out some other Doctrine resources below to learn more about Doctrine:

- Full User Manual - http://www.phpdoctrine.org/documentation/manual/0_11?one-page[8]
- API Documentation - http://www.phpdoctrine.org/documentation/api/0_11[9]
- Cheatsheet - http://www.phpdoctrine.org/Doctrine-Cheat-Sheet.pdf[10]
- Blog - http://www.phpdoctrine.org/blog[11]
- Community - http://www.phpdoctrine.org/community[12]
- Frequently Asked Questions - http://www.phpdoctrine.org/faq[13]
- Download - http://www.phpdoctrine.org/download[14]

4. http://www.phpdoctrine.org/documentation/manual/0_11?chapter=dql-doctrine-query-language
5. http://www.phpdoctrine.org/documentation/manual/0_11?chapter=basic-schema-mapping#constraints-and-validators
6. http://www.phpdoctrine.org/documentation/manual/0_11?chapter=hierarchical-data
7. http://www.phpdoctrine.org/documentation/manual/0_11?chapter=caching
8. http://www.phpdoctrine.org/documentation/manual/0_11?one-page
9. http://www.phpdoctrine.org/documentation/api/0_11
10. http://www.phpdoctrine.org/Doctrine-Cheat-Sheet.pdf
11. http://www.phpdoctrine.org/blog
12. http://www.phpdoctrine.org/community
13. http://www.phpdoctrine.org/faq
14. http://www.phpdoctrine.org/download

Chapter 3

symfony Doctrine Migrations

Chapter 4

Code Igniter and Doctrine

This tutorial will get you started using Doctrine with Code Igniter

Download Doctrine

First we must get the source of Doctrine from svn and place it in the system/database folder.

Listing 4-1

```
$ cd system/database
$ svn co http://svn.phpdoctrine.org/branches/0.11/lib doctrine
$ cd ..

// If you use svn in your project you can set Doctrine
// as an external so you receive bug fixes automatically from svn
$ svn propedit svn:externals database

// In your favorite editor add the following line
// doctrine http://svn.phpdoctrine.org/branches/0.11/lib
```

Setup Doctrine

Now we must setup the configuration for Doctrine and load it in system/application/config/database.php

Listing 4-2

```
$ vi application/config/database.php
```

The code below needs to be added under this line of code

Listing 4-3

```
$db['default']['cachedir'] = "";
```

Add this code

Listing 4-4

```
// Create dsn from the info above
$db['default']['dsn'] = $db['default']['dbdriver'] .
                        '://' . $db['default']['username'] .
                        ':' . $db['default']['password'].
                        '@' . $db['default']['hostname'] .
                        '/' . $db['default']['database'];

// Require Doctrine.php
require_once(realpath(dirname(__FILE__) . '/../..') . DIRECTORY_SEPARATOR
. 'database/doctrine/Doctrine.php');
```

```
// Set the autoloader
spl_autoload_register(array('Doctrine', 'autoload'));

// Load the Doctrine connection
Doctrine_Manager::connection($db['default']['dsn'],
$db['default']['database']);

// Set the model loading to conservative/lazy loading
Doctrine_Manager::getInstance()->setAttribute('model_loading',
'conservative');

// Load the models for the autoloader
Doctrine::loadModels(realpath(dirname(__FILE__) . '/..') .
DIRECTORY_SEPARATOR . 'models');
```

Now we must make sure system/application/config/database.php is included in your front controller. Open your front controller in your favorite text editor.

Listing 4-5
```
$ cd ..
$ vi index.php
```

Change the last 2 lines of code of index.php with the following

Listing 4-6
```
require_once APPPATH.'config/database.php';
require_once BASEPATH.'codeigniter/CodeIgniter'.EXT;
```

Setup Command Line Interface

Create the following file: system/application/doctrine and chmod the file so it can be executed. Place the code below in to the doctrine file.

Listing 4-7
```
$ vi system/application/doctrine
```

Place this code in system/application/doctrine

Listing 4-8
```
#!/usr/bin/env php
define('BASEPATH','.'); // mockup that this app was executed from ci ;)
chdir(dirname(__FILE__));
include('doctrine.php');
```

Now create the following file: system/application/doctrine.php. Place the code below in to the doctrine.php file.

Listing 4-9
```
require_once('config/database.php');

// Configure Doctrine Cli
// Normally these are arguments to the cli tasks but if they are set here
the arguments will be auto-filled
$config = array('data_fixtures_path'  =>  dirname(__FILE__) .
DIRECTORY_SEPARATOR . '/fixtures',
                'models_path'         =>  dirname(__FILE__) .
DIRECTORY_SEPARATOR . '/models',
                'migrations_path'     =>  dirname(__FILE__) .
DIRECTORY_SEPARATOR . '/migrations',
                'sql_path'            =>  dirname(__FILE__) .
```

```
DIRECTORY_SEPARATOR . '/sql',
                'yaml_schema_path'    =>  dirname(__FILE__) .
DIRECTORY_SEPARATOR . '/schema');

$cli = new Doctrine_Cli($config);
$cli->run($_SERVER['argv']);
```

Now we must create all the directories for Doctrine to use

Listing 4-10

```
// Create directory for your yaml data fixtures files
$ mkdir system/application/fixtures

// Create directory for your migration classes
$ mkdir system/application/migrations

// Create directory for your yaml schema files
$ mkdir system/application/schema

// Create directory to generate your sql to create the database in
$ mkdir system/application/sql
```

Now you have a command line interface ready to go. If you execute the doctrine shell script with no argument you will get a list of available commands

Listing 4-11

```
$ cd system/application
$ ./doctrine
Doctrine Command Line Interface

./doctrine build-all
./doctrine build-all-load
./doctrine build-all-reload
./doctrine compile
./doctrine create-db
./doctrine create-tables
./doctrine dql
./doctrine drop-db
./doctrine dump-data
./doctrine generate-migration
./doctrine generate-migrations-db
./doctrine generate-migrations-models
./doctrine generate-models-db
./doctrine generate-models-yaml
./doctrine generate-sql
./doctrine generate-yaml-db
./doctrine generate-yaml-models
./doctrine load-data
./doctrine migrate
./doctrine rebuild-db
$
```

On Microsoft Windows, call the script via the PHP binary (because the script won't invoke it automatically:

Listing 4-12

```
php.exe doctrine
```

Start Using Doctrine

It is simple to start using Doctrine now. First we must create a yaml schema file. (save it at schema with filename like : user.yml)

Listing 4-13
```
---
User:
  columns:
    id:
      primary: true
      autoincrement: true
      type: integer(4)
    username: string(255)
    password: string(255)
  relations:
    Groups:
      class: Group             # Class name. Optional if alias is the
class name
      local: user_id           # Local
      foreign: group_id        # Foreign
      refClass: UserGroup      # xRefClass for relating Users to Groups
      foreignAlias: Users      # Opposite relationship alias. Group
hasMany Users

Group:
  tableName: groups
  columns:
    id:
      primary: true
      autoincrement: true
      type: integer(4)
    name: string(255)

UserGroup:
  columns:
    user_id:
      type: integer(4)
      primary: true
    group_id:
      type: integer(4)
      primary: true
  relations:
    User:
      local: user_id        # Local key
      foreign: id           # Foreign key
      onDelete: CASCADE     # Database constraint
    Group:
      local: group_id
      foreign: id
      onDelete: CASCADE
```

Now if you run the following command it will generate your models in system/application/models

Listing 4-14
```
$ ./doctrine generate-models-yaml
generate-models-yaml - Generated models successfully from YAML schema
```

Now check the file system/application/models/generated/BaseUser.php. You will see a compclass definition like below.

Listing 4-15

```
/**
 * This class has been auto-generated by the Doctrine ORM Framework
 */
abstract class BaseUser extends Doctrine_Record
{

  public function setTableDefinition()
  {
    $this->setTableName('user');
    $this->hasColumn('id', 'integer', 4, array('primary' => true,
'autoincrement' => true));
    $this->hasColumn('username', 'string', 255);
    $this->hasColumn('password', 'string', 255);
  }

  public function setUp()
  {
    $this->hasMany('Group as Groups', array('refClass' => 'UserGroup',
                                            'local' => 'user_id',
                                            'foreign' => 'group_id'));

    $this->hasMany('UserGroup', array('local' => 'id',
                                      'foreign' => 'user_id'));
  }

}

// Add custom methods to system/application/models/User.php

/**
 * This class has been auto-generated by the Doctrine ORM Framework
 */
class User extends BaseUser
{
  public function setPassword($password)
  {
    $this->password = md5($password);
  }
}

/**
 * This class has been auto-generated by the Doctrine ORM Framework
 */
class UserTable extends Doctrine_Table
{
  public function retrieveAll()
  {
    $query = new Doctrine_Query();
    $query->from('User u');
    $query->orderby('u.username ASC');

    return $query->execute();
  }
}
```

Now we can create some sample data to load in to our application(this step requires you have a valid database configured and ready to go. The build-all-reload task will drop and recreate the database, create tables, and load data fixtures

Create a file in system/application/fixtures/users.yml

Listing 4-16
```
$ vi fixtures/users.yml
```

Add the following yaml to the file

Listing 4-17
```
---
User:
  jwage:
    username: jwage
    password: test
```

Now run the build-all-reload task to drop db, build models, recreate

Listing 4-18
```
$ ./doctrine build-all-reload
build-all-reload - Are you sure you wish to drop your databases? (y/n)
y
build-all-reload - Successfully dropped database named: "jwage_codeigniter"
build-all-reload - Generated models successfully from YAML schema
build-all-reload - Successfully created database named: "jwage_codeigniter"
build-all-reload - Created tables successfully
build-all-reload - Data was successfully loaded
```

Now we are ready to use Doctrine in our actual actions. Lets open our system/application/views/welcome_message.php and somewhere add the following code somewhere.

Listing 4-19
```
$user = new User();
$user->username = 'zYne-';
$user->setPassword('password');
$user->save();

$userTable = Doctrine::getTable('User');
$user = $userTable->findOneByUsername('zYne-');

echo $user->username; // prints 'zYne-'

$users = $userTable->retrieveAll();

echo $users->count(); // echo '2''
foreach ($users as $user)
{
  echo $user->username;
}
```